

GEONEX DTH-AUGER RODS

GEONEX DTH-AUGER RODS



GEONEX is manufacturing Auger Rods especially designed for Horizontal drilling for the most common casing sizes (139,7-1220 mm). Normally, the Auger rods are manufactured 3,0 m or 6,0 m long with API Reg connections. Thread types of other standards or with HEX rod ends are possible. We can also design Auger rods after your demands. We can repair or replace the screw blades on existing drill rods.

APPLICATIONS FOR GEONEX DTH-AUGER RODS

✓ Horizontal drilling

Especially for horizontal with DTH-hammer up to $\varnothing 1220$ mm casing pipe

✓ Drilling in different angles

Augers can be used to assist also in vertical or angular drillings

✓ Special drilling

Custom made special augers with stabilizers and unusual connections.

TECHNICAL INFORMATION

GEONEX DTH-Auger rods

	Dimension range	Connect
Ga auger rods	< $\varnothing 1220$ mm (48")	Api Reg, Beco, HEX HL 120, HEX HL 240
Auger rods	< $\varnothing 1220$ mm (48")	Api Reg, Beco, HEX HL 120, HEX HL 240
Hammer sleeve augers	< $\varnothing 1220$ (48")	Api Reg, Beco, HEX HL 120, HEX HL 240
Connections	2 3/8"-12"	Api Reg, Beco, HEX HL 120, HEX HL 240
Stabilizers	< $\varnothing 1016$ (40")	Api Reg, Beco