

GEONEX GR 120

GEONEX DTH-DRILLING ROTARY HEADS



Geonex Rotary Heads are engineered for DTH-Drilling. Design is compact and strong Engineered for both horizontal and vertical drilling. Rotary head can be mounted straight to feed carriage or as an option, there is also possibility for tilt function with cuttings collector. Speed switching valve option and different motor sizes also enables drilling of large diameter range. Rotary head has in-built air swivel with large hole through.

APPLICATIONS FOR GEONEX GR 120

✓ **HZR1000 horizontal drilling rig**

The GR120 rotary head is compatible with the HZR1000 horizontal drilling rig.

✓ **Vertical drilling, micro piling and big size piling rigs**

The rotary head is engineered for both horizontal and vertical drilling applications.

✓ **Special drilling rigs**

The GR120 can be attached to a variety of special drilling rigs from different brands.

TECHNICAL INFORMATION

Geonex GR 120

Weight kg (lb)	2500(5500)
Length (with out threads adapter) mm (ft in)	950 (3' 11/2")
Width mm (ft in)	960 (3' 2")
Height mm (ft in)	920 (3')
Thread connection (can be specified according to customer needs)	BECD 10" F / Api Reg 8 5/8" F
Max oil flow lpm (gpm)	500 (132)
Max pressure Bar (psi)	350(5075)
Hydraulic motor displacement cm ³ /r (cid)	2029 (124) / 1268 (77) / 761 (46)



GEONEX OY

Tel. +358 400 693 143

info@geonex.fi

Teollisuustie 9, FI-95600 Ylitornio, Finland

FOR MORE INFORMATION VISIT

www.geonex.fi

GEONEX GR 120

GEONEX DTH-DRILLING ROTARY HEADS

Geonex GR 120	
Max rotation torque, slow gear Nm (ftlb)	120000(88500)
Max rotation speed, slow gear r/min	16
Max rotation torque, med gear Nm (ftlb)	75000(55300)
Max rotation speed, med gear r/min	26
Max rotation torque, fast gear Nm (ftlb)	45000 (33190)
Max rotation speed, fast gear r/min	45
OPTION	Tilt function
OPTION	Sliding cuttings collector
OPTION	Different sub savers
OPTION	Speed switching valve



GEONEX OY

Tel. +358 400 693 143

info@geonex.fi

Teollisuustie 9, FI-95600 Ylitornio, Finland

FOR MORE INFORMATION VISIT

www.geonex.fi