# **GEONEX GR 120**

## GEONEX DTH-DRILLING ROTARY HEADS



Geonex Rotary Heads are engineered for DTH-Drilling. Design is compact and strong Engineered for both horizontal and vertical drilling. Rotary head can be mounted straight to feed carriage or as an option, there is also possibility for tilt function with cuttings collector. Speed switching valve option and different motor sizes also enables drilling of large diameter range. Rotary head has in-built air swivel with large hole through.

### **APPLICATIONS FOR GEONEX GR 120**



The GR120 rotary head is compatible with the HZR1000 horizontal drilling rig.

## 🗸 Vertical drilling, micro piling and

### big size piling rigs

The rotary head is engineered for both horizontal and vertical drilling applications.

### Special drilling rigs

The GR120 can be attached to a variety of special drilling rigs from different brands.

| Geonex GR 120  |                                   |
|--|-----------------------------------|
| Weight kg (lb)   | 2500(5500)                        |
| Length (with out threads adapter) mm (ft in)                     | 950 (3' 1 1/2")                   |
| Width mm (ft in)   | 960 (3' 2")                       |
| Height mm (ft in)  | 920 (3')                          |
| Thread connection (can be specified according to customer needs) | BECO 10" F / Api Reg 8 5/8" F     |
| Max oil flow lpm (gpm)   | 500 (132)                         |
| Max pressure Bar (psi)   | 350(5075)                         |
| Hydraulic motor displacement cm3/r (cid)                         | 2029 (124) / 1268 (77) / 761 (46) |



#### **GEONEX OY**

Tel. +358 400 693 143 info@geonex.fi Teollisuustie 9, FI-95600 Ylitornio, Finland FOR MORE INFORMATION VISIT

www.geonex.fi

## **TECHNICAL INFORMATION**

# **GEONEX GR 120**

## GEONEX DTH-DRILLING ROTARY HEADS

| Geonex GR 120                            |                            |
|--|----------------------------|
| Max rotation torque, slow gear Nm (ftlb) | 120000(88500)              |
| Max rotation speed, slow gear r/min      | 16                         |
| Max rotation torque, med gear Nm (ftlb)  | 75000(55300)               |
| Max rotation speed, med gear r/min       | 26                         |
| Max rotation torque, fast gear Nm (ftlb) | 45000 (33190)              |
| Max rotation speed, fast gear r/min      | 45                         |
| OPTION                                   | Tilt function              |
| OPTION                                   | Sliding cuttings collector |
| OPTION                                   | Different sub savers       |
| OPTION                                   | Speed switching valve      |



**GEONEX OY** 

Tel. +358 400 693 143 info@geonex.fi Teollisuustie 9, FI-95600 Ylitornio, Finland FOR MORE INFORMATION VISIT

www.geonex.fi