

GEONEX PP 90

GEONEX PP90 DIESEL DRIVEN HYDRAULIC POWER UNIT



PP90 is a compact and robust power pack. Harsh jobsite conditions set demands, that have been taken care of in the engineering. Power pack's small size and robust structure gives advantages in continuous lifting and transportation between jobsites. Two open circuit variable displacement hydraulic pumps can provide power to many various machines and applications. Tier 4 Final diesel engine emission class meets all the modern requirements.

APPLICATIONS FOR GEONEX PP 90



HZR 400 compatible

Originally PP90 is engineered to work with HZR400, and it is a perfect match for that drill rig.



Hydraulic power to other applications

PP90 can also provide hydraulic power to other applications with open pump circuit and LS-valves.



Electric power generator

PP90 can also be equipped with electric power generator to provide electric power for e.g. jobsite lighting and welding.

TECHNICAL INFORMATION

Geonex PP90	
Diesel engine	Deutz TCD 3,6
Engine displacement litres (cid)	3,6 / (220)
Engine power / Emission class	EU Stage 4 / Tier 4 Final
Max. engine speed (rpm)	2300
Pump 1 max. flow l/min (gpm)	160 (42)
Pump 2 max. flow l/min (gpm)	160 (42)
Hydraulic pump 1 & 2 max pressure bar (psi)	250 (3625)
Electric system	24 V



GEONEX OY

Tel. +358 400 693 143

info@geonex.fi

Teollisuustie 9, FI-95600 Ylitornio, Finland

FOR MORE INFORMATION VISIT

www.geonex.fi

GEONEX PP 90

GEONEX PP90 DIESEL DRIVEN HYDRAULIC POWER UNIT

Geonex PP90	
Hydraulic oil capacity l (gal)	165 (43)
Fuel capacity l (gal)	165 (43)
Lenght mm (ft in)	2170 (7' 2")
Width mm (ft in)	1240 (4' 1")
Height mm (ft in)	1900 (6' 3")
Weight kg (lb)	2400 (5300)
OPTION	Generator HG12kVA



GEONEX OY
Tel. +358 400 693 143
info@geonex.fi
Teollisuustie 9, FI-95600 Ylitornio, Finland

FOR MORE INFORMATION VISIT
www.geonex.fi

GEONEX PP 90

GEONEX PP90 DIESEL DRIVEN HYDRAULIC POWER UNIT

